

## TPWI EX2GD

### TPWI "EX" 2GD SERIES STAINLESS STEEL ATEX PALLET TRUCK SCALE



Pallet truck scales, with built-in electronic weighing, for dangerous areas classified as hazardous (ZONES 1 and 21 & 2 and 22) in accordance with Ex II 2G IIB T4 Gb X and Ex II 2D IIIC T197°C Db X.

The weight detection made with four Atex certified IP68 stainless steel load cells guarantees the best precision in any working environment.

Structure completely in STAINLESS steel.  
Available also CE-M APPROVED.

Working in cooperation with:

**PENTIMEX S.R.O.**

TUZINA, 26 - 97214 - TUZINA - SLOVAKIA  
Tel. 00421-46-5431793 Fax. 00421-46-5431135  
[info@pentimex.sk](mailto:info@pentimex.sk)

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Fork dimensions 1182 x 550 x 80 mm.
- Weighs about 135 kg.
- Bearing structure entirely in thick INOX sheet steel.
- Lifting pump in STAINLESS steel.
- Antistatic driving wheels.
- Double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 Atex certified shear-beam load cells.
- Weight indicator with waterproof IP68 STAINLESS STEEL case, easy to clean and resistant to harsh and corrosive environments; large high contrast 25mm LCD display, easily visible also in poor lighting conditions and waterproof membrane keypad, with 17 numerical/functional keys.
- Calibration and Set-Up parameters configurable from keyboard.
- Power supply through extractable battery, rechargeable in safe zone only, connectable and disconnectable from the weighing system also in hazardous area.
- 150-hour approximate operating time.
- Programmable auto power saving function.
- Equipped with 110/230Vac 50 Hz battery charger.

## MAIN FUNCTIONS

- Zeroing, Tare
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs accumulation
- Formulation
- +/- Checkweighing
- Percentage weighing
- Counting
- Hold

## AVAILABLE UPON PRICE ESTIMATE

- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

## DETAIL 1



Extractable battery

## DETAIL 2




## DETAIL 3





Orientable Head (OPTIONAL)

## DETAIL 4



VERSIONS

Available versions

	Codice	Max (kg)	d (kg)	<div>M</div> (kg)
	TPW20IEX2GD	500/1000/2000	0,2/0,5/1	--
	TPW20IEX2GDM <div>M</div>	1000/2000	--	0,5/1



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI AR GEO  
FRANCE sarl  
Nogent-sur-Marne

DINI AR GEO  
GMBH  
Sinsheim - Germany

DINI AR GEO  
UK Ltd  
Taunton - United Kingdom

DINI AR GEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI AR GEO  
WEIGHBRIDGES  
Calto (RO) - Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



**PENTIMEX S.R.O.**

TUZINA, 26 - 97214 - TUZINA - SLOVAKIA

Tel. 00421-46-5431793 Fax. 00421-46-5431135

info@pentimex.sk

SALES AND TECHNICAL ASSISTANCE SERVICE